


POLLUTION CONTROL BOARD

Phone : 020-25811627

Fax : 020-25811029

Email : ropune@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Jog Center, 3rd floor, Mumbai Pune Road,
Wakdevadi,

Pune - 411003

Orange/S.S.I

Date: 24/10/2013

Consent No: MPCB/13/08979

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&TM) Rules respectively].

.....
CONSENT is hereby granted to

M/s. Deccan Cold Storages (I) Pvt. Ltd.
Gat No. 569/570, MJ Kelwade
Tal. - Bhore, Dist - Pune.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 30.04.2015. *A. S. S. I.*

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Cold storage (Agri-Products)	1600.0	MT
2	Deep Frozen (Agri-Products)	1400.0	MT

(Without any food processing activity)

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed Nil.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 2.0 M³.

(iii) Trade Effluent : -NA-

(iv) Effluent Disposal:

(v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated sewage effluent to the following standards.

Page 1 of 6

- | | | | |
|-----------------------|---------------|-----|-------|
| (1) Suspended Solids | Not to exceed | 100 | mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The treated effluent shall be recycled to the maximum extent and remaining shall be disposed on land for gardening.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
		--NA--			

- (viii) **Other Conditions:**
- 1) Industry should monitor effluent quality regularly.
 - 2) Industry shall develop green belt of local species in 1/3rd of total area.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- | | | |
|------------------------------|-----|----------|
| (i) Domestic | ... | 2.00 CMD |
| (ii) Industrial Processing | ... | 0.00 CMD |
| (iii) Industrial Cooling | ... | 0.00 CMD |
| (iv) Agriculture / Gardening | ... | 0.00 CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Dust collector of sufficient capacity shall be provided to the source of particulate matter emission section to limit the following standard.

b) Standards for Stack Emissions:

- | | | | |
|--------------------|---------------|-----|--------------------|
| 1) SPM | Not to exceed | 150 | mg/Nm ³ |
| 2) SO ₂ | Not to exceed | 3.2 | kg/day - |

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.